

Thank you!



This brand new revolutionary product you are about to try along with our other aluminum storefront door products is going to save you lots of time and money.

No longer will it be necessary to leave unsightly holes or old locks on the door, nor will it be necessary to install a panic bar above or below the existing lock because you have no means of hiding the old holes. With our new snap in bridges and custom blank cover plates, and our hole filler discs you can remove the old hardware and cover up old unsightly cylinder and lock mounting holes and cavities in as little as 5 minutes.

Please take a minute to share your experience with our new bridges to help us help you. Your comments and critique will be greatly appreciated, and before and after photos could be rewarded with prizes.

ADDITIONAL PRODUCTS FROM THE GKL PRODUCTS LINE



GKL PRODUCTS

Manufacturer of the world famous "Hinge Doctor"

Ofc 888 446-4337 Fax 209 748-2405

P.O. Box 533, Herald, CA. 95638 sales@gklproducts.com



GKL Bridge Instructions

Note: For lock installations follow steps 1, 2, 3, and 4.

For blank faceplate installations follow steps 1, 2, 3, and 5

Step 1: Separate spacer from bridge and cleanup edges

Step 2: Insert the SK1 spanner key (not included) into the bridge and turn vertical

Step 3: Push bridge and spanner key all the way into the aluminum door stile and turn clockwise 90 degrees, then position either to the top or bottom and remove key. Done.

Step 4: To install lock

Just drop lock in as normal. Fasten with two 8 x 5/8" flathead mounting screws supplied and install cylinders.

Step 5: to install blank faceplate instead of lock

Insert spacers in bridges then put blank faceplate on and check height. If low add supplied shims as needed. Install 8-5/8" screws. Done.

► Questions call: Tel.: 888 446-4337

